

## OIL-LESS COMPRESSORS






### SINGLE SURGERY

### 1 SURGERY @ 5BAR

**AC100 (service kit requirement: 'SERV-AIR1-A' / 'SERV-AIR1-B')** All compressors are 1~, 3~ is available on request.

Receivers are coated with BioCote® Silver Ion Technology which delivers highly effective protection against microbes such as bacteria and mould. Permanent antimicrobial protection, Guaranteed.

Cattani compressors when correctly specified will deliver the minimum requirements of 50 litres/minute per chair (at 5bar pressure) when running simultaneously.

	<b>AC100</b> <b>Includes:</b> <b>Dryer</b> <b>H13130</b>	No. of Surgeries: 1 surgery No. of Cylinders: Single cylinder No. of Dryers: 1 dryer Output power: 1~ 50Hz 0.55kW - 3.8A Produced air: 67.5N l/min (pressure at 5 real bar) Air Tank Volume: 30 litres Noise level: 70dB(A) Dimensions: W620 D460 H720 (mm) Net Weight: 47kg Gross Weight: 61kg	
	<b>Extended Warranty</b> <b>EXT-COMP1</b>	Optional additional 2 Year Warranty must be purchased at point of sale with AC100 or AC100Q Compressors, cannot be added on after purchase date. Subject to servicing, proof may be required.	
	<b>AC100Q</b> <b>Includes:</b> <b>Dryer</b> <b>Noise Reducing Cover</b> <b>H13150 (*1)</b>	No. of Surgeries: 1 surgery No. of Cylinders: Single cylinder No. of Dryers: 1 dryer Output power: 1~ 50Hz 0.55kW - 3.8A Produced air: 67.5N l/min (pressure at 5 real bar) Air Tank Volume: 30 Litres Noise level: 63dB(A) Dimensions: W660 D600 H860 (mm) Net Weight: 57kg Gross Weight: 72kg	
	<b>Sound Reducing Cabinet</b> <b>010800</b>	Noise level 52dB(A) W840 D700 H887 (mm) Net Weight 84kg	
	<b>Regulator Gauge and Fitting Kit</b> <b>070REG</b>	Includes 1 metre of nylon tube & fittings to 8mm & 15mm pipe	
	<b>Upgrade Kit</b> <b>070RHTM</b>	HTM2022 Compliant Inclusive of medical sterile filter DOP efficiency >99.9999% Particle removal 0.01 micron Water separator eliminating 99% bulk water at continuous pressure to ISO 12500-4:2009 Particulate filter particle retention 99.999% to ISO 12500-3:2009 Safety valve atmospheric discharge brass safety relief valve Designed to achieve in excess of -20° dew point (atmospheric) 3/8" BSP pharmaceutical test point and line pressure gauge	
	<b>HEPA H14 in-line filter</b> <b>168429</b>	HEPA H14 filter element for compressor heads	

## OIL-LESS COMPRESSORS










### MULTIPLE SURGERY

### 3 SURGERIES RUNNING SIMULTANEOUSLY @ 5BAR

**AC200 (service kit requirement: 'SERV-AIR2-A' / 'SERV-AIR2-B')** All compressors are 1~, 3~ is available on request.

Receivers are coated with BioCote® Silver Ion Technology which delivers highly effective protection against microbes such as bacteria and mould. Permanent antimicrobial protection, Guaranteed.

Cattani compressors when correctly specified will deliver the minimum requirements of 50 litres/minute per chair (at 5bar pressure) when running simultaneously.

	<b>AC200</b> <b>Includes:</b> <b>Dryer</b> <b>H13230</b>	No. of Surgeries: 3 surgeries running simultaneously No. of Cylinders: 2 cylinder No. of Dryers: 1 dryer Output power: 1~ 50Hz 1.2kW - 7.7A Produced air: 160N l/min (pressure at 5 real bar) Air Tank Volume: 30 Litres Noise level: 71dB(A) Dimensions: W620 D460 H720 (mm) Net Weight: 54kg Gross Weight: 68kg	
	<b>Extended Warranty</b> <b>EXT-COMP2</b>	Optional additional 2 Year Warranty must be purchased at point of sale with AC200 or AC200Q Compressors, cannot be added on after purchase date. Subject to servicing, proof may be required.	
	<b>AC200Q</b> <b>Includes:</b> <b>Dryer</b> <b>Noise Reducing Cover</b> <b>H13250 (*1)</b>	No. of Surgeries: 3 surgeries running simultaneously No. of Cylinders: 2 cylinder No. of Dryers: 1 dryer Output power: 1~ 50Hz 1.2kW - 7.7A Produced air: 160N l/min (pressure at 5 real bar) Air Tank Volume: 30 Litres Noise level: 63dB(A) Dimensions: W660 D600 H860 (mm) Net Weight: 64kg Gross Weight: 79kg	
	<b>Sound Reducing Cabinet</b> <b>010800</b>	Noise level 52dB(A) W840 D700 H887 (mm) Net Weight 84kg	
	<b>Regulator Gauge and Fitting Kit</b> <b>070REG</b>	Includes 1 metre of nylon tube & fittings to 8mm & 15mm pipe	
	<b>Upgrade Kit</b> <b>070RHTM</b>	<b>HTM2022 Compliant</b> Inclusive of medical sterile filter DOP efficiency >99.9999% Particle removal 0.01 micron Water separator eliminating 99% bulk water at continuous pressure to ISO 12500-4:2009 Particulate filter particle retention 99.999% to ISO 12500-3:2009 Safety valve atmospheric discharge brass safety relief valve Designed to achieve in excess of -20° dew point (atmospheric) 3/8" BSP pharmaceutical test point and line pressure gauge	
	<b>HEPA H14 in-line filter</b> <b>168429</b>	HEPA H14 filter element for compressor heads	